CRANE SCALES

10kg to 50ton

(30, 40, 50 ton)



CRANE SCALES with Wireless Indicator

Features:


- Wireless transmission maximum operating distance between the Scale and Indicator is 50 mtr.
- All specifications are same as standard crane scales (CCS) except there is no display on the sale and there is no remote keyboard.
- Power indication LED on the scale.
- Battery & charger for the loadcell & transmitter inside the scale.
- Weight display on the desktop indicator along with controls.
- RS-232 interface in the indicator (Optional).
- Indicator with optional battery backup.
- Date & time entry facility.
- Storage of weights in memory upto 100 samples.
- Display hold facility.

Common Specifications:

| MODELS | CAPACITY | ACCURACY | DIMENSION | | | ExF | NET WT. | |
|------------|----------|----------|-----------|-----|-----|-----|---------|------|
| | | | Н | A | В | C | | (Kg) |
| CCS-30T10K | 30 ton | 10Kg | 1110 | 160 | 260 | 90 | 500x310 | 156 |
| CCS-40T20K | 40 ton | 20Kg | 1200 | 180 | 220 | 110 | 440x410 | 235 |
| CCS-50T20K | 50 ton | 20Ka | 1310 | 200 | 270 | 110 | 440X410 | 280 |

Taring Range: Up to full capacity Response time: 5 seconds

Power Req: 90-250V, 50/60Hz, 10 Watt Operating Temperature: 10 to 45 deg C



All Specifications and designs are subject to change for improvement.



301, Punit Indl. Premises, Turbhe Naka, Navi Mumbai - 400 705.

Tel.:+91 22 6139 3000 (100 lines)

Fax:+91 22 2761 8421

E-mail: info@contechindia.in / sales@contechindia.in

Website: www.contechindia.com

